

HPE Networking Comware Switch Series 5600 HI

HPE Networking Comware Switch 48P 100M/1G/2.5G/5G/10GBase-T PoE8 4QSFP+ 1 Slot 5600HI (SOS35A)



What's new

- Multigigabit 100M/1/2.5/5/10G options with PoE8. Granular, higher throughput, and switching capacity of up to 600 Mpps and 1440 Gbps, higher traffic rates and improved network performance.
- DRNI combines multiple physical switches into one virtual distributed-relay system for doubling aggregate bandwidth, faster forwarding, resiliency, and high availability.
- Industry-standard MACsec AES 256 support, higher MAC port binding, AAA authentications (including RADIUS authentication), and link group capacity for improved end-to-end network security.
- iNQA measures network packet loss performance and provides visibility

Overview

The HPE FlexNetwork 5600 HI Switch Series delivers superior performance using Multigigabit, PoE8, MACsec, AES 256 encryption, link flexibility, and scalability at the access layer of medium and large enterprise campus networks. Additional modules can be included for increased capacity. This series offers improved resiliency with DRNI and IRF, better reliability and performance in user Quality of Service (QoS), enhanced security with hardware-based MACsec and AAA authentication, impressive efficiency with dual redundant power supplies, embedded network management using Smart MC and enhanced network visibility using IMC.

into real-time application performance and health.

- SmartMC provides centralized network management and maintains dispersed network edge devices at no additional cost.
- VXLAN and EVPN enable both isolation and greater scalability of L2/L3 overlay services and multicast.

Features

Multigigabit PoE8 High-density Switches

HPE FlexNetwork 5600 HI Switch Series provides medium and large enterprise networks with 24/48 port 1G/2.5G/5G/10GBASE-T connectivity options, thereby resulting in high density and flexibility.

90W PoE8 supports a wide variety of applications such as virtual desktop infrastructure (VDI) or Internet of Things (IoT).

Delivers up to 600 Mpps of packet forwarding rate and up to 1440 Gbps of port switching capacity for improved network performance.

Supports jumbo frames with a frame size of up to 10000 bytes while improving the performance of large data transfers.

Supports equal-cost multipath that enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth.

Highly Available and Scalable Access Layer Switches

The HPE FlexNetwork 5600 HI Switch Series uses IRF that supports virtualization of up to nine physical switches into one logical device for simpler, flatter, and more agile networks.

DRNI, an IEEE standard-based solution, enables link aggregation from multiple switches to implement device-level link backup for node redundancy. DRNI also simplifies network topology by virtualizing two physical devices into a logical device.

Dual, redundant, and hot-swappable power supplies maintain a dynamic and highly available network.

Virtual Routing Redundancy Protocol (VRRP) is available where groups of two routers can dynamically back each other up to create highly available routed environments.

VXLAN and EVPN allow greater flexibility to integrate into existing networks, better scalability without redesigning the underlay network, enhanced security to restrict attacks, and improved performance specially in spine-leaf architectures.

Rich QoS Features

The HPE FlexNetwork 5600 HI Switch Series supports operations, administration, and maintenance (OAM), MPLS, VPLS, and In-Service Software Upgrade (ISSU) for business continuity and improving manageability.

Advanced classifier based QoS is available to group traffic using multiple match criteria based on Layer 2 and 3 information; it applies QoS policies such as setting priority level and rate limit to selected traffic on a port, VLAN, or the entire switch.

Extensive traffic prioritization with strict priority (SP) queuing, weighted round robin (WRR), weighted deficit round robin (WDRR), SP+WDRR, and SP+WRR are supported.

Broadcast control and limitation of broadcast traffic rate can reduce unwanted network traffic.

Comprehensive Security and Simplified Management

HPE FlexNetwork 5600 HI Switch Series supports AAA authentication (including RADIUS authentication) and dynamic or static binding of user identifiers such as user account, IP address, MAC address, VLAN, and port number for increased security.

Supports methods including 802.1X and MAC authentication and encryption for greater device security and policy-driven application authentication, along with per-user access control Lists (ACLs) that provide identity-driven security and access control.

Dynamic ARP protection with functions such as ARP detection and ARP packet validation that block broadcasts from unauthorized hosts, prevent eavesdropping or theft of network data.

Single-pane management via HPE IMC provides a consistent network experience and OpenFlow enables integration with mainstream cloud platforms or a third-party controller for flexible network customization and automated management.

SmartMC, an embedded network management tool, supports a web-based GUI to simplify operations and facilitate centralized management at no additional cost. It offers features such as configuration backup, software version management, and seamless switch replacement.

Technical specifications	HPE Networking Comware Switch 48P 100M/1G/2.5G/5G/10GBase-T PoE8 4QSFP+ 1 Slot 5600HI
Product Number	SOS35A
Differentiator	48 fixed 100M/1G/2.5G/5G/10GBase-T UPoE Ports min=0 \ max=4 QSFP+ Transceivers 1 port expansion module slot 2 Power Supply Slots (Min1/Max2) Including 3 Fan Trays 1U - Height
Power consumption	Dual AC 2333W
Heat dissipation	Ranges from 221 BTU/ hour to 7960 BTU/ hour depending on power supply configuration
Input voltage	AC: 90 VAC to 264 VAC, DC: -36 VDC to 72 VDC
Ports	48 x 100M/1G/2.5G/5G/10GBASE-T (PoE8) + 4 x QSFP Plus + 1 expansion slot
Latency	< 5 us (1000Mb), < 3 us (10Gbps) <1.2 us (40Gbps)
Routing/switching capacity	1440 Gbps
Stacking capabilities	9
Throughput	600 Mpps
Memory and processor	2 GB SDRAM packet buffer size: 6 MB, 1G flash
Power supply	2 Power Supply Slots (Min1/Max2), JG544A (720W), JG545A (1110W)
PoE capability	90W PoE power per port
Management features	This switch series includes Smart Management Center (SmartMC) at no additional cost and combined with HPE Intelligent Management Center (IMC), provides both embedded network management and enhanced network visibility.
Operating temperature	23°F to 113°F (-5°C to 45°C)
Weight	6.05 kg
Product dimensions	4.37 x 44 x 46 cm
Warranty	These switches support Limited Lifetime warranty for details on warranty and software releases available with your product purchase, please refer to hpe.com/networking/support

HPE Services

No matter where you are in your transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From strategy and planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

Advisory & Professional services

Experts can help you map out your path to hybrid cloud and optimize your operations.

Managed services

HPE runs your IT operations, giving you unified control, so can focus on innovation.

Support services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources.

- **HPE Complete Care Service:** a modular service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals. All delivered by an assigned team of HPE experts.
- **HPE Tech Care Service:** the operational service experience for HPE products. The service provides access to product specific experts, an AI driven digital experience, and general technical guidance to help reduce risk and search for ways to do things better.
- **HPE Multivendor Services:** Single point of accountability for managing on-site hardware and software support for multivendor products. HPE experts help manage your IT across technologies and platforms for HPE and non-HPE technologies, acting as the single point of contact for your IT operational needs.

Lifecycle Services

Address your specific IT deployment project needs with tailored project management and deployment services.

HPE Education Services

Training and certification designed for IT and business professionals across all industries. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options

Defective Media Retention is optional and allows you to retain Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

HPE GreenLake

[HPE GreenLake edge-to-cloud platform](#) is HPE's market-leading as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model, on premises, fully managed in a pay per use model.

If you are looking for more services, like **IT financing solutions**, please [explore them here](#).

For additional technical information,
available models and options, please
reference the QuickSpecs

Visit [HPE.com](https://www.hpe.com)

Chat now

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product.

PSN1014716348IDEN, January 05, 2026.

HEWLETT PACKARD ENTERPRISE

[hpe.com](https://www.hpe.com)

