



* Product configuration and appearance may vary

JUNIPER SSR400 LINE OF ROUTERS

Product description

The modern enterprise demands more from its network. It needs powerful, secure, and easily manageable connectivity that can keep pace with the demands of cloud-enabled applications and a distributed workforce. Legacy routers are no longer up to the task, creating complexity and compromising performance. The SSR400 challenges this status quo.

HPE Juniper Networking SSR Series Routers provide the foundation for HPE Juniper AI-native SD-WAN. They enable enterprises to build service-centric fabrics that connect users to applications with unparalleled efficiency. When deployed at branch offices the SSR400 Router, provides a service-centric control plane and a service-aware data plane. The router offers robust IP routing, a fully featured policy engine, and proactive analytics. The result is a next-generation SD-WAN solution that lets you fundamentally reimagine branch networking.

Product overview

Networks today require powerful, secure, and easily manageable connectivity for distributed branches. The Juniper Networking SSR400 Router is an AI-native Session Smart Router that consolidates routing, SD-WAN, and next-generation firewall capabilities into a single, compact, fanless device. This all-in one solution simplifies IT operations, accelerates deployment, and ensures a secure, high performance experience, all managed via the Mist platform's cloud.

Uncompromising security

The SSR400 is built on a zero trust SD-WAN architecture. It includes a full-fledged next-generation firewall (NGFW) with deny-by-default access controls and military-grade encryption that protects against threats from the first packet. This unified security fabric goes beyond the limitations of add-on security solutions. It simplifies operations while delivering the protection modern enterprises demand.

Revolutionary performance and efficiency

The SSR400 leverages Session Smart Technology to deliver a highly efficient service fabric, enabling intelligent, sub-second traffic rerouting. This provides superior performance and ensures a quick boot-up time of under two minutes for rapid traffic recovery after an outage.

Proactive AI-native operations

The SSR400 is driven by [Marvis AI](#), transforming network management from reactive to proactive. It leverages AI Forensics to deliver unparalleled visibility into service level experiences (SLEs) and provide automated root cause analysis. The SSR400 can identify over 8,500 applications and ensure each one gets the performance it needs. This intelligent automation dramatically reduces operational overhead and the need for manual troubleshooting.

Streamlined simplicity

Designed with the "Branch in a Box" concept in mind, the SSR400 is a compact, fanless device ideal for quiet, small branch and retail locations. Its physical simplicity is matched by its operational elegance. With flexible templates, automated zero touch provisioning (ZTP), and centralized management from the Mist platform's cloud, it dramatically simplifies deployment and ongoing management.

Architecture and key components

By combining the AI-native intelligence of Juniper WAN Assurance with the Session Smart Router, enterprises gain industry-leading automation and insight to ensure the best user, device, and application experiences in their branch and remote locations. The Juniper WAN Assurance cloud service simplifies operations, provides superior visibility into end-user experiences, and reduces the mean time to repair for SD-WAN issues.

The SSR400 line of routers provides the hardware foundation for this service-centric fabric. These appliances feature a service-centric control plane and service-aware data plane that offer robust IP routing, a feature-rich policy management engine, improved visibility, and proactive analytics. This architecture moves beyond the limitations of traditional, tunnel-based solutions by delivering a single, unified platform for powerful and secure connectivity.

SSR400 fixed configuration appliances

The fixed configuration appliances in the SSR400 line are designed for a variety of branch sizes:

- **The SSR400:** Ideal for small branches and retail locations
- **The SSR440:** Designed to serve the needs of medium-sized branches

These appliances run the FIPS 140-3 Level 2 compliant Session Smart Router software, which provides secure and resilient WAN connectivity as a core component of the HPE Juniper Networking AI-native SD-WAN solution.

WAN Assurance

WAN Assurance is a cloud service that brings AI-native automation and service levels to SSR Series Routers, complementing the HPE Juniper Networking AI-native SD-WAN solution. WAN Assurance transforms IT operations from reactive troubleshooting to proactive remediation, turning insights into actions and delivering operational simplicity with seamless integration into existing deployments.

- SSR Series SD-WAN routers, deployed as secure SD-WAN edge devices, deliver the rich streaming telemetry that provides the insights needed for WAN health metrics and anomaly detection. This data is leveraged within the Mist platform's cloud and Marvis AI engine, driving simpler operations, reducing mean time to repair (MTTR), and providing greater visibility into end-user experiences.
- Insights derived from SSR Series SD-WAN gateway telemetry data allow WAN Assurance to compute unique "User Minutes" that indicate whether users are having a good experience.
- [Marvis AI Assistant](#) for WAN allows you to ask direct questions like, "Why is my Zoom call bad?" and provides complete insights, correlation, and actions.
- Marvis Actions identify and summarize issues such as application latency conditions, congested WAN circuits, or negotiation mismatches.

For detailed features and benefits of WAN Assurance, see the [WAN Assurance data sheet](#).

Simplifying branch deployments (secure connectivity/SD-WAN)

SSR400 Routers deliver fully automated SD-WAN to both enterprises and service providers.

- Configuration templates and ZTP features simplify branch network connectivity for initial deployment and ongoing management.
- SSR400 line of SD-WAN routers offer best-in-class secure connectivity.
- The SSR400 line of SD-WAN routers efficiently utilize multiple links and load balance traffic across the enterprise WAN, blending traditional MPLS with other connectivity options such as broadband internet, leased lines, WCDMA/LTE/5G, and more. Policy- and application-based forwarding capabilities enforce business rules created by the enterprise to steer application traffic toward a preferred path.

Features and benefits

Table 1. Features and benefits

Category	Features
System and network services	SNAT/DNAT, destination NAT, shared NAT pool, IPv4/IPv6, DHCP client, DHCP relay, DHCP server, DHCP server extensions, DHCPv6 PD, DNS client, PPPoE, Proxy ARP, NAT traversal, BFD, inline flow performance monitoring, extended firewall pinhole, path MTU discovery, MSS auto adjust, DSCP based service identification for IPsec
Advanced services	Secure Vector Routing (SVR), Multipoint SVR, IPv6 SVR, overlapping IP service segmentation, Ethernet over SVR, application identification
Routing	Service based routing, static routing, BGPv4, BGP route reflector, BGP graceful restart, BGP over SVR, BGP route map, BGP prefix list, OSPFv2, BGP VRF, OSPF VRF
Traffic engineering	Traffic scheduling and shaping, flow policing and shaping, packet marking (DiffServ), service rate limiting
Network firewall	Distributed stateful firewall, distributed and automated access control, fine-grained segmentation/tenancy, ICSA network firewall certified, ICMP blackhole
IDS/IPS and URL filtering	Intrusion Detection System/Intrusion Prevention System (IDS/IPS) and URL filtering capabilities are available through the Advanced Security Pack
Secure edge connectors	Seamless connections to Juniper Secure Edge or third-party SSE
Application identification	HTTP/S domain-based identification, Microsoft 365 identification, DNS based identification, application categorization
Session encryption	Session metrics, network metrics, cellular metrics, peer path SLA, MOS score, session analytics, SSL/TLS metrics, session IPFIX records Session Payload Encryption (AES-256, AES-128), session/route authentication (HMAC-SHA1, HMAC-SHA256, HMAC-SHA-256-128), adaptive encryption, rekeying, FIPS 140-3 validated, enhanced replay attack protection, transport-based encryption Path selection, (SLA, MoS, average latency), load balancing using proportional and hunt, session migration, session duplication, session duplication for non-SVR, session duplication for inter-node links, MOS for VoIP, Path of last resort, session optimization, session reliability, service health learning, service route redundancy
Monitoring	Monitoring agent, SNMPv2, Syslog, audit logs
Management and remote access	GUI, CLI, REST, remote access over SVR (cellular), upgrade rollback, zero touch provisioning, remote service packet capture, user-defined configuration templates, role-based access control
AAA	Local registry, LDAP

Specifications

Table 2. Hardware specifications

Specification	SSR400	SSR400-C
Connectivity		
Encrypted throughput	300 Mbps	300 Mbps
Total onboard ports	10x1GbE	10x1GbE
Onboard RJ-45 ports	8x1GbE	8x1GbE
Onboard small form-factor pluggable (SFP) transceiver ports	2x1GbE	2x1GbE
HA ports with MACsec capability	10x1GbE	10x1GbE
Console (USB-C)	1	1
USB ports (type C)	1	1
PoE+ ports	2	2
Cellular	N/A	WCDMA/LTE/5G
Dimensions and power		
Form factor	Desktop	Desktop
Size (WxHxD)	11.81 x 1.3 x 7.52 in. (30.00 x 3.30 x 19.10 cm)	11.81 x 1.3 x 7.52 in. (30.00 x 3.30 x 19.10 cm)
Redundant PSU	No	No
Power supply	AC (external)	AC (external)
Maximum PoE power	60W	60W
Airflow/cooling	Fanless	Fanless
Operating environment	0°C to 50°C	0°C to 40°C
Storage temperature	-40°C to 70°C	-40°C to 70°C
Operating altitude	Up to 2000m (6562 ft) at 50°C	Up to 2000m (6562 ft) at 40°C

Specification	SSR440	SSR440-2AC	SSR440-C	SSR440-C-2AC
Connectivity				
Encrypted throughput	300–500 Mbps	300–500 Mbps	300–500 Mbps	300–500 Mbps
Total onboard ports	10x1GbE	10x1GbE	10x1GbE	10x1GbE
Onboard RJ-45 ports	8x1GbE	8x1GbE	8x1GbE	8x1GbE
Onboard small form-factor pluggable (SFP) transceiver ports	2x1GbE	2x1GbE	2x1GbE	2x1GbE
HA ports with MACsec capability	10x1GbE	10x1GbE	10x1GbE	10x1GbE
Console (USB-C)	1	1	1	1
USB ports (type C)	1	1	1	1
PoE+ ports	2	2	2	2
Cellular	N/A	N/A	WCDMA/LTE/5G	WCDMA/LTE/5G
Dimensions and power				
Form factor	Desktop	Desktop	Desktop	Desktop
Size (WxHxD)	11.81 x 1.3 x 7.52 in. (30.00 x 3.30 x 19.10 cm)	11.81 x 1.3 x 7.52 in. (30.00 x 3.30 x 19.10 cm)	11.81 x 1.3 x 7.52 in. (30.00 x 3.30 x 19.10 cm)	11.81 x 1.3 x 7.52 in. (30.00 x 3.30 x 19.10 cm)
Redundant PSU	No	Yes (180W)	No	Yes (180W)
Power supply	AC (external)	2 x redundant AC (external)	AC (external)	2 x redundant AC (external)
Maximum PoE power	60W	60W	60W	60W
Airflow/cooling	Fanless	Fanless	Fanless	Fanless
Operating environment	0°C to 50°C	0°C to 50°C	0°C to 40°C	0°C to 40°C
Storage temperature	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
Operating altitude	Up to 2000 meters (6562 ft) at 50°C	Up to 2000 meters (6562 ft) at 50°C	Up to 2000 meters (6562 ft) at 40°C	Up to 2000 meters (6562 ft) at 40°C

Electromagnetic compatibility

- FCC 47 CFR Part 15
- ICES-003 / ICES-GEN
- BS EN 55032
- BS EN 55035
- EN 300 386 V1.6.1
- EN 300 386 V2.2.1
- BS EN 300 386
- EN 55032
- CISPR 32
- EN 55035
- CISPR 35
- IEC/EN 61000 Series
- IEC/EN 61000-3-2
- IEC/EN 61000-3-3
- AS/NZS CISPR 32
- VCCI-CISPR 32
- BSMI CNS 15936
- EN 301 489-1
- EN 301 489-52
- EN 301 489-17
- KS X 3126
- KS X 3124
- KS C 9835 (Old KN 35)
- KS C 9832 (Old KN 32)
- KS C 9610
- QCVN 18:2022
- QCVN 131:2022

Safety

- CAN/CSA-C22.2 No. 62368-1 and 60950-1
- UL 62368-1 and 60950-1
- IEC 62368-1
- CFR, Title 21, Chapter 1, Subchapter J, Part 1040
- REDR c 1370 OR CAN/CSA-E 60825-1-Part 1
- IEC 60825-1
- IEC 60825-2

About HPE

HPE is a leader in essential enterprise technology, bringing together the power of AI, cloud, and networking to help organizations achieve more. As pioneers of possibility, our innovation and expertise advance the way people live and work. We empower our customers across industries to optimize operational performance, transform data into foresight, and maximize their impact. Unlock your boldest ambitions, with HPE.

Discover more at [HPE.com](https://hpe.com)

[Visit HPE.com](https://hpe.com)

[Chat now](#)

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. All third-party marks are property of their respective owners.

a00154678ENW, Rev. 1

HEWLETT PACKARD ENTERPRISE

hpe.com

